

Strong

- Hurricane rated up to +/- 70 psf
- Single in swing 3'0" x 7'0" openings
 Hardware:
 - Corbin Russwin ML2000, ML20600, ML20900 Series mortise locks with latch bolt and dead bolt
 - SARGENT 11 Line Series cylindrical locks
 - SARGENT 7800, 8200, R8200 Series mortise locks with latch bolt and dead bolt
- Single out swing 3'0" x 7'0" opening
 Hardware:
 - Yale 7150 and 7250 Series exit device
- Pair in swing 6'0" x 7'0" openings

Active leaf:

- Corbin Russwin ML2000, ML20600, ML20900 Series mortise locks with latch bolt and dead bolt
- SARGENT 7800, 8200, R8200 Series mortise locks with latch bolt and dead bolt

Inactive leaf:

- Rockwood 556 WS Series flush bolts

- Steel stiffened core adds strength, durability and security to any building

Beautiful

- No vertical weld marks on door face sheets for a blemish free surface
- Factory Finish available with standard and custom colors to choose from

Green

- Energy Efficient opening (U-Value 0.38*) significantly reduces cooling and heating costs
 - First steel stiffened hollow metal swinging door to qualify for GreenGuard Gold
- * U-Value of 0.38 achieved when installed in CURRIES CURRISeal frame


1502 12th Street NW | Mason City, IA 50401
 Phone: 641-423-1334 | Fax: 641-424-8305
 www.curries.com

Experience a safer
 and more open world



Energy Efficient and Hurricane Rated

The Curries Trio-E (777E Series) door meets Texas Department of Insurance (TDI) most stringent code requirements for hurricane force winds and flying debris up to +/-70. Plus, Trio-E helps increase a buildings thermal efficiency and reduce energy loss. Energy is a major cost for building owners. The Trio-E door can provide significant energy savings on new or retrofit projects while helping to protect the owner's investment from severe weather.



Log onto www.curries.com or contact an ASSA ABLOY Door Security Solutions Representative for more information.