

## Hurricane

Single +/-50 psf design pressure  
4'0" x 8'0" maximum

Pairs +/-60 psf design pressure  
8'0" x 8'0" maximum with hollow  
metal or hardware mullion

## Testing

CURRIES products are third party  
independently tested and  
certified by these standards:

TAS 202  
ASTM E331

## Doors Options

607 Polystyrene  
707 Polystyrene  
727 Temperature Rise  
747 Steel Stiffened  
777 Trio  
777E Trio-E

## Glazing Options

Maximum 24" x 66" of visible glass  
using Glasslam™ Safety Plus® II  
Light kits are limited to CURRIES  
type 1, 2, or 3 kits.

## Hardware Options

CORBIN RUSSWIN  
MARKAR  
McKINNEY  
RIXSON  
ROCKWOOD  
SARGENT  
SECURITRON  
VING CARD ELSAFE  
YALE  
YALE YM

1502 12th Street NW  
Mason City • IA 50401  
Phone: 641-423-1334  
Fax: 641-424-8305



## ***CURRIES Adds Water Infiltration Solution to Their Line of Hurricane Products for Door Openings.***



CURRIES has added a water infiltration door solution for the Florida market, focused on Miami Dade and Broward Counties (HVHZ–High Velocity Hurricane Zone)

**Find more information on [www.curries.com](http://www.curries.com)**

Experience a safer  
and more open world